


TK-7360HV / 8360HU V2.0
VHF/UHF Conventional Mobile Radios



All 360 series mobiles include:

- Standard Microphone (KMC-35)
- Mounting Bracket
- DC Cable (KCT-23M)
- 15A Fuse
- Instruction Manual
- Standard Warranty: 2 Years*

* All Accessories / options: 1 Year

GENERAL FEATURES

- 50 W (136-174 MHz) Model
- 45 W (450-520 MHz) Model
- Conventional & LTR® Zones
- 10-Character Alphanumeric Aliases
- Backlit LCD & Keys
- Function/Status LCD Icons
- Blue Function / Status LED
- Transmit /Busy / Call Alert LED
- 10 Programmable Function Keys
- Emergency / AUX Key
- Front Panel Speaker
- Companded Audio
- Voice Inversion Scrambler Built-in
- 16 Scrambler Codes (per CH)
- Encryption / Board Control
- Emergency Call Features
- Lone Worker Alert
- DTMF Encode / Decode
- Special Alert Tone Patterns
- Busy Channel Lockout
- Time Out Timer
- Timed Power Off
- DB15 Accessory Interface
- 8 Programmable I/O Ports
- Ignition Sense
- Public Address / Horn Alert Output
- MIL-Spec Standard Mic
- MIL-Spec 12-Key DTMF Mic Option
- Windows® Programming & Tuning
- Easy Option Ports (26-pin)
- Cloning
- Voice Guide & Storage (Option)
- MIL-STD-810 C/D/E/F/G
- IP54 Water & Dust Intrusion

CONVENTIONAL ZONES

- 128 Channels / 128 Zones
- QT / DQT
- Two-Tone Decode
- Single & Two-Tone Encode
- Operator Selectable Tone
- Single Priority Scan
- Single / Multi-Zone Scan

TRUNKED ZONES

- 128 GID / 128 Zones
- Kenwood LTR® Feature

FleetSync® /II (FM)

- PTT ID Digital ANI
- Selective Call & Group Call
- Paging Call
- Status Messaging
- Emergency Status
- Caller ID Display
- Input / Output Status Messages
- FleetSync® GPS Ready
- Send GPS PF Key
- PTT ID & Emergency GPS Reporting
- GPS Auto Reporting

MDC-1200

- PTT ID Digital ANI
- Caller ID Display
- Emergency Status
- Radio Check
- Radio Inhibit

MODEL		LIST
TK-7360HVK	136-174 MHz 50W, 128 CH / 128 Zone Conventional	467.00
TK-8360HUK	450-520 MHz 45W, 128 CH / 128 Zone Conventional	484.00

MOBILE INSTALLATION ACCESSORIES		LIST
KCT-60M	DB15-to-15pin Molex Adapter Cable	29.00
KCT-18	Ignition sense cable (requires KCT-60M Acc. Cable Option)	13.70
KCT-36	Extension Cable for KCT-34/35/39/40M/60M; 117.6 inches (9.8 ft)	43.75
KLF-2	Line Filter (suppresses alternator whine, 25dB, 25A max).	42.00
KMB-10	Key lock adapter	26.30

CONTROL STATION INSTALLATION ACCESSORIES		LIST
KMC-9C	Control Station Desktop Microphone (8-pin mod. plug)	86.00
KMB-24	Control Station Mounting Case for KPS-15 Power Supplies (mobile mounting hardware included)	42.00
KPS-15	DC Switching Power Supply (117/230 VAC; 23A max. continuous, 25A peak)	173.00

MICROPHONES AND SPEAKERS **LIST**

KMC-35	MIL-SPEC Standard electret mobile microphone (8-pin mod. plug) - same as supplied	52.50
KMC-36	MIL-SPEC Standard electret mobile microphone with 12-key DTMF (8-pin mod. plug)	94.50
KMC-9C	Control Station Desktop Microphone (8-pin mod. plug)	86.00
KES-3	External speaker (compact low profile; black case; 3.5 mm phono plug-in)	44.25
KES-5	External speaker, 40W max input Note: requires KCT-60M installed	61.25

FleetSync® AVL **LIST**

GPS15XL-W	Garmin Internal GPS Receiver Board for FleetSync® AVL Note: <ul style="list-style-type: none"> • Conventional operation only • Requires GA25 MCX GPS antenna • Refer to www.garmin.com for GPS-15L-W technical specifications. • Option: Order L-1690 for Kenwood Long Beach installation 	130.25
GA25MCX	Garmin On-dash Style Magnetic base GPS Antenna for GPS15XL-W Note: shipped loose only; Install GA25MCX antenna to GPS15XL-W before vehicle install.	62.00

OPTION MODULES **LIST**

VGS-1	Voice Guide and Storage Unit	87.50
-------	------------------------------	-------

SERVICE RELATED ACCESSORIES **LIST**

KPG-46UM	USB Programming interface cable	158.50
KPG-135DK	Windows® Programming Software for TK-7360/8360	103.25

Contact Kenwood Parts for Price and Availability 800-367-7514 on the following:		
E30-3382-05	Clone cable	---
J29-0662-03	Mounting bracket - same as supplied w/ radio (order N99-2039-05 for mounting screw set)	---

INSTALLATION / TUNING CHARGES **LIST**

L-1689	TK-7360/8360 Programming (with basic TX/RX check)	37.50
L-1690	Install Garmin GPS15XL-W in 360-Series mobile for FleetSync® AVL	100.00
L-1693	Install VGS-1 Voice Guide & Storage Unit Note: VGS-1 installation precludes any ANI or encryption board installation	25.00